

Cisco RV160 VPN Router and RV160W Wireless-AC VPN Router Datasheet



CONTENT

Content	1
Overview	2
Appearance	2
Prominent feature/Differentiator/Capability	3
Features and benefits	3
Product specifications	3
Ordering information	7
Where to Buy	9
Sources	9

Contact Us

Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166 /

Fax: +852-3050-1066 (Hong Kong)

Email: cisco@router-switch.com (Sales Inquiries)

ccie-support@router-switch.com (CCIE Technical Support)

OVERVIEW

The Cisco® Small Business RV Series has a long tradition with our partners and customers. The new Cisco RV160 and RV160W routers continue the tradition with a blend of performance, security, and quality, plus simple configuration, deployment, and flexibility.

Reliable, secure routing is required for any business, regardless of its size. Like all of the routers in the Cisco Small Business RV Series, the RV160 and RV160W are perfect for the small business, home office, teleworker, retail, office, restaurant, small hospitality, medical/dental, real estate, or small branch deployment.

The RV160 and RV160W models are easy to configure and deploy, offer low-touch remote deployment, are supported by our FindIT network platform, and deliver performance unheard of in a 100-level RV Series model. The all-new user interface is easy to use and quicker to configure.

These models have a dual-core processor that provides performance usually found only in more expensive solutions. A Small Form-Factor Pluggable (SFP) WAN port provides flexible connectivity and investment protection. Like the other models in the portfolio, the RV160 and RV160W include standard features such as a business-grade Stateful Packet Inspection (SPI) firewall, VPN security (IP Security [IPsec], Point-to-Point Tunneling Protocol [PPTP], and OpenVPN), content filtering, and device wizards to make an easy setup even easier.

The RV160 is a wired model, offering a high-performance user experience at an affordable cost. The RV160W offers the same plus 2x2 Wireless AC. This all-in-one model offers fantastic wireless performance and range for the small business and remote office.

APPEARANCE

Figure 1. Cisco RV160 VPN Router



Figure 2. Cisco RV160W VPN Router



PROMINENT FEATURE/DIFFERENTIATOR/CAPABILITY

The Cisco RV160 and RV160W VPN routers are high-performance models that combine business-class features with security, reliability, and overall value. Both models are perfect for the small business or small home office network.

A new user interface helps you get up and running with Internet access in minutes. You will enjoy reliable, highly secure connectivity that is so transparent you may not be aware of it.

FEATURES AND BENEFITS

- The RV160 provides wired connectivity
- The RV160W is a wireless VPN router, with 2x2 802.11ac wireless
- Flexible SFP/RJ-45 combination WAN ports
- Native 4-port switch
- High-performance Gigabit Ethernet ports, enabling large file transfers and multiple users

PRODUCT SPECIFICATIONS

Table 1. Specifications

Description	Specification
Ethernet WAN	1 RJ-45 SFP Gigabit Ethernet combination port
Ethernet LAN	4 RJ-45 Gigabit Ethernet ports

Console port	1 RJ-45 port	
Switch	Power on/off	
Cabling type	Category 5 or better	
LEDs	Power, VPN, WAN, LAN	
Operating system	Linux	
LAN		
VLANs	16	
Port security	Yes, 802.1X	
IPv6	Dual stack, 6rd, 6in4	
WAN	Dynamic Host Configuration Protocol (DHCP) client, static IP, Point-to-Point Protocol over Ethernet (PPPoE), PPTP, Layer 2 Tunneling Protocol (L2TP)	
WLAN	2x2 wireless 802.11ac (RV160W)	
Security	Security	
Firewall	SPI firewall	
	Port forwarding and triggering	
	Denial-of-Service prevention (DoS)	
Access control	IP access control lists	
Secure management	HTTPS, username/password complexity	
User privileges	Two levels of access: Admin and guest	
Network		
Network protocols	Dynamic Host Configuration Protocol (DHCP) server	
	Point-to-Point Protocol over Ethernet (PPPoE)	
	Point-to-Point Tunneling Protocol (PPTP)	
	Layer 2 Tunneling Protocol (L2TP)	
	DNS proxy	
	DHCP relay agent	
	Internet Group Management Protocol (IGMP) proxy and multicast	
	forwarding	
	Rapid Spanning Tree Protocol (RSTP)	
	Dynamic DNS (TZO, DynDNS, 3322.org, No-IP)	
	Network Address Translation (NAT), Port Address Translation (PAT)	

	One-to-one NAT
	Port management
	Port mirroring
	Software-configurable DMZ to any LAN IP address
	Session Initiation Protocol (SIP) Application-Layer Gateways (ALG)
Routing protocols	Static routing, IGMP proxy
	Dynamic routing
	Dynamic DNS (ChangeIP, DynDNS, No-IP)
	Routing Information Protocol (RIP) v1 and v2
	RIP for IPv6 (RIPng)
	Inter-VLAN routing
NAT protocol	Port Address Translation (PAT), Network Address Port Translation (NAPT)
	Policy NAT
	Port forwarding, one-to-one NAT, VPN NAT Traversal, Session Initiation
	Protocol (SIP), ALG, FTP ALG
VPN	
Gateway-to-gateway IPsec VPN	10 IPsec tunnels
Client-to-gateway IPsec VPN	10 IPsec tunnels
IPsec VPN	Internet Key Exchange (IKE) v2, Generic Routing Encapsulation (GRE), hub and spoke supported
PPTP VPN	10 PPTP VPN tunnels
OpenVPN	Support for the OpenVPN server
Encryption	Triple Data Encryption Standard (3DES), Advanced Encryption Standard (AES) with 128, 192, and 256-bit keys encryption
VPN pass-through	IPsec, PPTP, and L2TP pass-through
Quality of Service (QoS)	
QoS	802.1p port-based priority on LAN port, application-based priority on WAN port
	• 4 queues
	Differentiated Services Code Point (DSCP) support
	Class of service (CoS)
	Bandwidth management for service prioritization

Jumbo frame support	Supports jumbo frames on Gigabit ports – at least 1536B	
Performance		
NAT throughput	600 Mbps	
Concurrent sessions	15,000	
IPsec VPN throughput	50 Mbps	
Configuration	Configuration	
Web-based user interface	Browser-based configuration (HTTP/HTTPS)	
Management	Web-based user interface, Simple Network Management Protocol (SNMP) v3, Bonjour, Universal Plug and Play (PnP) FindIT support for monitoring and management	
Event logging	Local, syslog, email alerts	
Network diagnostics	Ping, traceroute, DNS lookup	
Upgradability	Firmware upgradable via browser UI, imported/exported file, USB, Cisco FindIT	
System time	Network Time Protocol (NTP), Daylight Savings, manual entry	
Language support	User interface support: English	
Environmental		
Power	RV160: 12VDC/1.5A RV160W: 12VDC/2A	
Operating temperature	0° to 40°C (32° to 104°F)	
Storage temperature	-20° to 70°C (-4° to 158°F)	
Operating humidity	10% to 85% noncondensing	
Storage humidity	5% to 90% noncondensing	
Certifications	Safety: UL 60950-1 CAN/CSA-C22.2 No. 60950-1 IEC 60950-1 EN 60950-1 Radio approvals: FCC Part 15.247, 15.407 RSS-210 (Canada)	

• EN 300.328, EN 301.893 (Europe)
AS/NZS 4268.2003 (Australia and New Zealand) EMI and susceptibility
(Class B):
• FCC Part 15.107 and 15.109
• ICES-003 (Canada)
• EN 301.489-1 and -17 (Europe)

ORDERING INFORMATION

Table 2. Ordering information

Product number	Product description	
RV160 Router		
RV160-K9-NA	Cisco RV160 VPN Router for United States, Canada, Columbia, Mexico, Chile, Taiwan	
RV160-K9-G5	Cisco RV160 VPN Router for EU (CE Mark) 32 countries, Ukraine, Hong Kong, Singapore, Thailand, Vietnam, Philippines, Indonesia, Malaysia, Saudi Arabia, UAE, South Africa	
RV160-K9-AU	Cisco RV160 VPN Router for Australia, New Zealand	
<u>RV160-K9-AR</u>	Cisco RV160 VPN Router for Argentina	
<u>RV160-K9-BR</u>	Cisco RV160 VPN Router for Brazil	
RV160-K9-CN	Cisco RV160 VPN Router for China	
<u>RV160-K9-IN</u>	Cisco RV160 VPN Router for India	
RV160-K9-JP	Cisco RV160 VPN Router for Japan	
<u>RV160-K9-KR</u>	Cisco RV160 VPN Router for Korea	
<u>RV160-K8-RU</u>	Cisco RV160 VPN Router for Russian Federation	
RV160W Router		

RV160W-A-K9-NA	Cisco RV160W VPN Router for United States, Canada, Columbia, Mexico
RV160W-E-K9-G5	Cisco RV160W VPN Router for EU (CE Mark) 32 Countries, Hong Kong, Singapore, Thailand, Vietnam, Philippines
RV160W-A-K9-AU	Cisco RV160W VPN Router for Australia, New Zealand
RV160W-A-K9-AR	Cisco RV160W VPN Router for Argentina
RV160W-A-K9-BR	Cisco RV160W VPN Router for Brazil
RV160W-C-K9-CN	Cisco RV160W VPN Router for China
RV160W-I-K9-IN	Cisco RV160W VPN Router for India
RV160W-E-K9-JP	Cisco RV160W VPN Router for Japan
RV160W-R-K8-RU	Cisco RV160W VPN Router for Russian Federation

WHERE TO BUY

Want to buy this series of products? please contact:

- Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: cisco@router-switch.com (Sales Inquiries)

Or visit: Cisco RV160 and RV160W VPN Router

About us

Router-switch.com (HongKong Yejian Technologies Co., Ltd), founded in 2002, is one of the biggest Global Network Hardware Supplier. We are a leading provider of network products with 18,000+ customers in over 200 countries. We provide original new and used network equipments (Cisco, Huawei, HPE, Dell, Juniper, EMC, etc.), including Routers, Switches, Servers, Storage, Telepresence and Videoconferencing, IP Phones, Firewalls, Wireless APs & Controllers, EHWIC/HWIC/VWIC Cards, SFPs, Memory & Flash, Hard Disk, Cables, and all kinds of network solutions related products.

SOURCES

https://www.cisco.com/c/en/us/products/collateral/routers/rv160-vpn-router/datasheet-c78-74 1410.html