



**Huawei**

AP7052DN & AP7152DN

**Access Points**

Datasheet



## Product Overview

Huawei AP7052DN and AP7152DN are the latest-generation technology-leading 802.11ac Wave 2 wireless access points (APs) that support 4x4 MIMO four spatial streams, and 2.4G-to-5G switchover. In dual-5G mode, the device rate can reach up to 3.46 Gbit/s. Both APs support smooth evolution from 802.11n to 802.11ac. They meet the bandwidth requirements of large-bandwidth services such as High Definition (HD) video streams, multimedia, and desktop cloud services, delivering smooth and high-quality wireless services to enterprise users. With industry-leading capabilities in terms of signal coverage, access density, and operation stability, the APs provide high-quality mobile cloud access services to help customers build the optimal wireless network. The AP7052DN and AP7152DN comply with 802.11ac Wave 2 and provide the 5GE uplink port, easily eliminating uplink bandwidth bottlenecks. They are more intelligent, secure, and easier to use. The AP7052DN and AP7152DN deliver industry-leading performance in a rugged, attractive enclosure and are ideal for indoor coverage scenarios, such as enterprise office and education scenarios.



AP7052DN



AP7152DN

- 802.11ac Wave 2 compliance, MU-MIMO (4SU-4MU), delivering services simultaneously on 2.4G and 5G radios; 800 Mbit/s at 2.4 GHz; 1.73 Gbit/s at 5 GHz; and 2.53 Gbit/s for the device.
- 2.4G-to-5G switchover. In dual-5G mode, the device rate can reach up to 3.46 Gbit/s.
- 5GE uplink interface that can connect to a 100M/1000M/2.5G interface, to improve the service load capability.
- Dual PoE power supply for backup.
- Built-in Bluetooth (BLE4.1) to implement precise location with eSight.
- USB interface used for external power supply and storage.
- IoT module to allow for flexible expansion of IoT applications.
- Supports the Fat, Fit, and cloud modes and enables Huawei cloud-based management platform to manage and operate APs and services on the APs, reducing network O&M costs.

## Feature Descriptions

### 5G uplink

The AP provides the 5GE uplink interface, supporting the uplink bandwidth required for an 802.11ac Wave 2 AP.

### IoT extension

The AP provides one IoT slot that allows for extension using IoT modules such as ZigBee and RFID, implementing short-distance, lower-power consumption IoT applications.

## MU-MIMO

The AP supports MU-MIMO. MU-MIMO technology allows an AP to send data to multiple STAs at the same time (currently, most 802.11n/11ac Wave 1 APs can only send data to one STA simultaneously). The technology marks the start of the 802.11ac Wave 2 era.

## GE access

The APs support the 80-MHz bandwidth mode. Frequency bandwidth increase brings extended channels and more sub-carriers for data transmission, and a 2.16 times higher rate. Support for High Quadrature Amplitude Modulation (HQAM) at 256-QAM increases the 5 GHz radio rate to 1.73 Gbit/s. The throughput of the AP is four times that of traditional 802.11n APs under the similar conditions.

## Cloud-based management

Huawei Cloud Managed Network (CMN) Solution consists of the cloud management platform and a full range of cloud managed network devices. The cloud management platform provides various functions including management of APs, tenants, applications, and licenses, network planning and optimization, device monitoring, network service configuration, and value-added services.

## High Density Boost technology

Huawei uses the following technologies to address challenges in high-density scenarios, including access problems, data congestion, and poor roaming experience:

- **Interference suppression**
  - Huawei's Clear Channel Assessment (CCA) optimization technology reduces the possibility of air port resources shared by multiple devices, allows higher user access, and improves the throughput.
- **Air interface performance optimization**
  - In high-density scenarios where many users access the network, increased number of low-rate STAs consumes more resources on the air port, reduces the AP capacity, and lowers user experience. Therefore, Huawei APs will check the signal strength of STAs during access and rejects access from weak-signal STAs. At the same time, the APs monitor the rate of online STAs in real time and forcibly disconnect low-rate STAs so that the STAs can reassociate with APs that have stronger signals. The terminal access control technology can increase air interface use efficiency and allow access from more users.
- **5G-prior access (Band steering)**
  - The APs support both 2.4G and 5G frequency bands. The 5G-prior access function enables an AP to steer STAs to the 5 GHz frequency band first, which reduces load and interference on the 2.4 GHz frequency band, improving the user experience.
- **Load balancing between APs**
  - After the load balancing function is enabled, the AC distributes users evenly to APs based on user quantity and traffic volume. Traffic load is therefore balanced among APs to ensure stable AP performance.
- **Smart roaming**
  - Smart roaming technology is based on the 802.11k, 802.11v and 802.11r technologies and allows STAs to connect to APs with stronger signals, improving user experience and the overall performance of the wireless network.
- **Agile Beam**
  - Agile antenna polarization beam automatic adaption.

## Wired and wireless dual security guarantee

To ensure data security, Huawei APs integrate wired and wireless security measures and provide comprehensive security protection.

- **Authentication and encryption for wireless access**
  - The APs support WEP, WPA/WPA2-PSK, WPA/WPA2-802.1x, and WAPI authentication/encryption modes to ensure security of the wireless network. The authentication mechanism is used to authenticate user identities so that only authorized users can access network resources. The encryption mechanism is used to encrypt data transmitted over wireless links to ensure that the data can only be received and parsed by expected users.
- **Analysis on non-Wi-Fi interference sources**
  - Huawei APs can analyze the spectrum of non-Wi-Fi interference sources and identify them, including baby monitors, Bluetooth devices, digital cordless phones (at 2.4 GHz frequency band only), wireless audio transmitters (at both the 2.4 GHz and 5 GHz frequency bands), wireless game controllers, and microwave ovens. Coupled with Huawei eSight, the precise locations of the interference sources can be detected, and the spectrum of them displayed, enabling the administrator to remove the interference in a timely manner.
- **Rogue device monitoring**
  - Huawei APs support WIDS/WIPS, and can monitor, identify, defend, counter, and perform refined management on the rogue devices, to provide security guarantees for air interface environment and wireless data transmission.
- **AP access authentication and encryption**
  - The AP access control ensures validity of APs. The CAPWAP link protection and DTLS encryption provide security assurance, improving data transmission security between the AP and the AC.

## Automatic radio calibration

Automatic radio calibration allows an AP to collect signal strength and channel parameters of surrounding APs and generate AP topology according to the collected data. Based on interference from authorized APs, rogue APs, and non-Wi-Fi interference sources, each AP automatically adjusts its transmit power and working channel to make the network operate at the optimal performance. In this way, network reliability and user experience are improved.

## Automatic application identification

Huawei APs support smart application control technology and can implement visualized control on Layer 4 to Layer 7 applications.

- **Traffic identification**
  - Coupled with Huawei ACs, the APs can identify over 1600 common applications in various office scenarios. Based on the identification results, policy control can be implemented on user services, including priority adjustment, scheduling, blocking, and rate limiting to ensure efficient bandwidth resource use and improve quality of key services.
- **Traffic statistics collection**
  - Traffic statistics of each application can be collected globally, by SSID, or by user, enabling the network administrator to know application use status on the network. The network administrator or operator can implement visualized control on service applications on smart terminals to enhance security and ensure effective bandwidth control.

**Basic Specifications**..... //**Hardware specifications**

Item	Description	
Technical specifications	Dimensions (H x W x D)	52 mm x 220 mm x 220 mm
	Weight	AP7052DN:1.68 kg AP7152DN:1.7kg
	Interface type	1 x 10/100/1000M self-adaptive Ethernet interface (RJ45) 1 x 100/1000M/2.5G/5G self-adaptive Ethernet interface (RJ45) 1 x Management console port (RJ45) 1 x USB interface
	IoT slot	One slot, supporting extension using ZigBee and RFID modules
	Built-in Bluetooth	BLE4.1
	LED indicator	Indicates the power-on, startup, running, alarm, and fault status of the system.
Power specifications	Power input	DC: 42.5 V to 57 V PoE power supply: in compliance with IEEE 802.3at/bt; dual PoE power supply.
	Maximum power consumption	DC/802.3bt power supply: 33 W (Excluding the output power of the USB port) 802.3at power supply: 25.5 W (The USB function and the 5 Gbit/s mode of network ports are unavailable. The IoT card power is lower than 0.5 W.)  <b>NOTE</b> The actual maximum power consumption depends on local laws and regulations. In 802.3at power supply mode, radio power is managed in self-adaptive mode.
Environmental specifications	Operating temperature	-10°C to +50°C
	Storage temperature	-40°C to +70°C
	Operating humidity	5% to 95% (non-condensing)
	Dustproof and waterproof grade	IP41
	Altitude	-60 m to +5000 m
	Atmospheric pressure	53 kPa to 106 kPa
Radio specifications	Antenna type	AP7052DN: built-in dual-band omnidirectional antennas AP7152DN: external dual-band omnidirectional antennas
	Antenna gain	AP7052DN: 2.4G / 5G (switchable): 2 dBi/ 2.8 dBi      5G (non-switchable): 2.8 dBi AP7152DN: 2.4G / 5G (switchable): 2 dBi/ 3.5 dBi      5G (non-switchable): 4 dBi
	Maximum number of SSIDs for each radio	16
	Maximum number of users	≤ 512

Item		Description
Radio specifications	Maximum transmit power	2.4G / 5G (switchable): 26 dBm/ 21 dBm (combined power) 5G (non-switchable): 24 dBm (combined power)  <b>NOTE</b> The actual transmit power depends on local laws and regulations.
	Power increment	1 dBm
	Receiver sensitivity	2.4 GHz 802.11b : -104 dBm @ 1 Mbit/s; -95 dBm @ 11 Mbit/s
		2.4 GHz 802.11g: -96 dBm @ 6 Mbit/s; -77 dBm @ 54 Mbit/s
		2.4 GHz 802.11n (HT20): -95 dBm @ MCS0; -75 dBm @ MCS31
		2.4 GHz 802.11n(HT40): -92 dBm @ MCS0; -73 dBm @ MCS31
		5 GHz 802.11a : -95 dBm @ 6 Mbit/s; -79 dBm @ 54 Mbit/s
		5 GHz 802.11n (HT20): -94 dBm @ MCS0; -74 dBm @ MCS31
		5 GHz 802.11n (HT40): -93 dBm @ MCS0; -71 dBm @ MCS31
		5 GHz 802.11ac (VHT20): -94 dBm @ MCS0NSS1; -70 dBm @ MCS8NSS4
		5 GHz 802.11ac (VHT40): -91 dBm @ MCS0NSS1; -67 dBm @ MCS9NSS4
		5 GHz 802.11ac (VHT80): -88 dBm @ MCS0NSS1; -62 dBm @ MCS9NSS4
		5 GHz 802.11ac (VHT160): -85 dBm @ MCS0NSS1; -62 dBm @ MCS9NSS2

**Basic Specifications**..... //**Softwarespecifications****Fat/Fit AP mode**

Item	Description
WLAN features	<p>Compliance with IEEE 802.11a/b/g/n/ac/ac Wave 2</p> <p>Dual-5G mode: 3.46 Gbit/s</p> <p>Maximum ratio combining (MRC)</p> <p>Space time block code (STBC)</p> <p>Cyclic Delay Diversity (CDD)/Cyclic Shift Diversity (CSD)</p> <p>Beamforming</p> <p>MU-MIMO</p> <p>Low-density parity-check (LDPC)</p> <p>Maximum-likelihood detection (MLD)</p> <p>Frame aggregation, including A-MPDU (Tx/Rx) and A-MSDU (Tx/Rx)</p> <p>802.11 dynamic frequency selection (DFS)</p> <p>Short guard interval (GI) in 20 MHz, 40 MHz, 80 MHz, 160 MHz, and 80+80 MHz modes</p> <p>Priority mapping and packet scheduling based on a Wi-Fi Multimedia (WMM) profile to implement priority-based data processing and forwarding</p> <p>Automatic and manual rate adjustment</p> <p>WLAN channel management and channel rate adjustment</p> <p>Automatic channel scanning and interference avoidance</p> <p>Service set identifier (SSID) hiding</p> <p>Signal sustain technology (SST)</p> <p>Unscheduled automatic power save delivery (U-APSD)</p> <p>Control and Provisioning of Wireless Access Points (CAPWAP) in Fit AP mode</p> <p>Automatic login in Fit AP mode</p> <p>Extended Service Set (ESS) in Fit AP mode</p> <p>Wireless distribution system (WDS) in Fit AP mode</p> <p>Mesh networking in Fit AP mode</p> <p>Multi-user CAC</p> <p>Hotspot2.0</p> <p>802.11k and 802.11v smart roaming</p> <p>802.11r fast roaming (<math>\leq 50</math> ms)</p> <p>WAN authentication escape. In local forwarding mode, this function retains the online state of existing STAs and allows access of new STAs when APs are disconnected from an AC, ensuring service continuity.</p>

Item	Description
Network features	<ul style="list-style-type: none"> <li>Compliance with IEEE 802.3ab</li> <li>Auto-negotiation of the rate and duplex mode and automatic switchover between the Media Dependent Interface (MDI) and Media Dependent Interface Crossover (MDI-X)</li> <li>Compliance with IEEE 802.1q</li> <li>SSID-based VLAN assignment</li> <li>VLAN trunk on uplink Ethernet ports</li> <li>Management channel of the AP uplink port in tagged and untagged mode</li> <li>DHCP client, obtaining IP addresses through DHCP</li> <li>Tunnel data forwarding and direct data forwarding</li> <li>STA isolation in the same VLAN</li> <li>Access control lists (ACLs)</li> <li>Link Layer Discovery Protocol (LLDP)</li> <li>Uninterrupted service forwarding upon CAPWAP channel disconnection in Fit AP mode</li> <li>Unified authentication on the AC in Fit AP mode</li> <li>AC dual-link backup in Fit AP mode</li> <li>Network Address Translation (NAT) in Fat AP mode</li> <li>IPv6 in Fit AP mode</li> <li>Soft Generic Routing Encapsulation (GRE)</li> <li>IPv6 Source Address Validation Improvements (SAVI)</li> </ul>
QoS features	<ul style="list-style-type: none"> <li>Priority mapping and packet scheduling based on a Wi-Fi Multimedia (WMM) profile to implement priority-based data processing and forwarding</li> <li>WMM parameter management for each radio</li> <li>WMM power saving</li> <li>Priority mapping for upstream packets and flow-based mapping for downstream packets</li> <li>Queue mapping and scheduling</li> <li>User-based bandwidth limiting</li> <li>Adaptive bandwidth management (automatic bandwidth adjustment based on the user quantity and radio environment) to improve user experience</li> <li>Smart Application Control (SAC) in Fit AP mode</li> <li>Airtime scheduling</li> <li>Support for Microsoft Lync APIs and high voice call quality through Lync API identification and scheduling</li> </ul>

Item	Description
Security features	<p>Open system authentication</p> <p>WEP authentication/encryption using a 64-bit, 128-bit, or 152-bit encryption key</p> <p>WPA/WPA2-PSK authentication and encryption (WPA/WPA2 personal edition)</p> <p>WPA/WPA2-802.1x authentication and encryption (WPA/WPA2 enterprise edition)</p> <p>WPA-WPA2 hybrid authentication</p> <p>WAPI authentication and encryption</p> <p>Wireless intrusion detection system (WIDS) and wireless intrusion prevention system (WIPS), including rogue device detection and countermeasure, attack detection and dynamic blacklist, and STA/AP blacklist and whitelist</p> <p>802.1x authentication, MAC address authentication, and Portal authentication</p> <p>DHCP snooping</p> <p>Dynamic ARP Inspection (DAI)</p> <p>IP Source Guard (IPSG)</p> <p>802.11w Protected Management Frames (PMFs)</p> <p>Application identification</p>
Maintenance features	<p>Unified management and maintenance on the AC in Fit AP mode</p> <p>Automatic login and configuration loading, and plug-and-play (PnP) in Fit AP mode</p> <p>WDS zero-configuration deployment in Fit AP mode</p> <p>Mesh network zero-configuration deployment in Fit AP mode</p> <p>Batch upgrade in Fit AP mode</p> <p>Telnet</p> <p>STelnet using SSH v2</p> <p>SFTP using SSH v2</p> <p>Local AP management through the serial interface</p> <p>Web local AP management through HTTP or HTTPS in Fat AP mode</p> <p>Real-time configuration monitoring and fast fault location using the NMS</p> <p>SNMP v1/v2/v3 in Fat AP mode</p> <p>System status alarm</p> <p>Network Time Protocol (NTP) in Fat AP mode</p>
BYOD	<p> <b>NOTE</b></p> <p>The AP supports bring your own device (BYOD) only in Fit AP mode.</p> <p>Identifies the device type according to the organizationally unique identifier (OUI) in the MAC address.</p> <p>Identifies the device type according to the user agent (UA) information in an HTTP packet.</p> <p>Identifies the device type according to DHCP options.</p> <p>The RADIUS server delivers packet forwarding, security, and QoS policies according to the device type carried in the RADIUS authentication and accounting packets.</p>

Item	Description
Location service	<p> <b>NOTE</b></p> <p>The AP supports the locating service only in Fit AP mode.</p> <p>Locates tags manufactured by AeroScout or Ekahau.</p> <p>Locates Wi-Fi terminals.</p> <p>Works with eSight to locate rogue devices.</p>
Spectrum analysis	<p> <b>NOTE</b></p> <p>The AP supports spectrum analysis only in Fit AP mode.</p> <p>Identifies interference sources such as baby monitors, Bluetooth devices, digital cordless phones (at 2.4 GHz frequency band only), wireless audio transmitters (at both the 2.4 GHz and 5 GHz frequency bands), wireless game controllers, and microwaves.</p> <p>Works with eSight to perform spectrum analysis on interference sources.</p>

### Cloud-based management mode

Item	Description
WLAN features	<p>Compliance with IEEE 802.11a/b/g/n/ac/ac Wave 2</p> <p>Dual-5G mode: 3.46 Gbit/s</p> <p>Maximum ratio combining (MRC)</p> <p>Space time block code (STBC)</p> <p>Beamforming</p> <p>Low-density parity-check (LDPC)</p> <p>Maximum-likelihood detection (MLD)</p> <p>Frame aggregation, including A-MPDU (Tx/Rx) and A-MSDU (Tx/Rx)</p> <p>802.11 dynamic frequency selection (DFS)</p> <p>Priority mapping and packet scheduling based on a Wi-Fi Multimedia (WMM) profile to implement priority-based data processing and forwarding</p> <p>WLAN channel management and channel rate adjustment</p> <p> <b>NOTE</b></p> <p>For detailed management channels, see the Country Code &amp; Channel Compliance Table.</p> <p>Automatic channel scanning and interference avoidance</p> <p>Service set identifier (SSID) hiding</p> <p>Signal sustain technology (SST)</p> <p>Unscheduled automatic power save delivery (U-APSD)</p> <p>Automatic login</p>


Item	Description
Network features	<ul style="list-style-type: none"> <li>Compliance with IEEE 802.3ab</li> <li>Auto-negotiation of the rate and duplex mode and automatic switchover between the Media Dependent Interface (MDI) and Media Dependent Interface Crossover (MDI-X)</li> <li>Compliance with IEEE 802.1q</li> <li>SSID-based VLAN assignment</li> <li>DHCP client, obtaining IP addresses through DHCP</li> <li>STA isolation in the same VLAN</li> <li>Access control lists (ACLs)</li> <li>Unified authentication on the Agile Controller</li> <li>Network Address Translation (NAT)</li> </ul>
QoS features	<ul style="list-style-type: none"> <li>Priority mapping and packet scheduling based on a Wi-Fi Multimedia (WMM) profile to implement priority-based data processing and forwarding</li> <li>WMM parameter management for each radio</li> <li>WMM power saving</li> <li>Priority mapping for upstream packets and flow-based mapping for downstream packets</li> <li>Queue mapping and scheduling</li> <li>User-based bandwidth limiting</li> <li>Airtime scheduling</li> </ul>
Security features	<ul style="list-style-type: none"> <li>Open system authentication</li> <li>WEP authentication/encryption using a 64-bit, 128-bit, or 152-bit encryption key</li> <li>WPA/WPA2-PSK authentication and encryption (WPA/WPA2 personal edition)</li> <li>WPA/WPA2-802.1x authentication and encryption (WPA/WPA2 enterprise edition)</li> <li>WPA-WPA2 hybrid authentication</li> <li>802.1x authentication, MAC address authentication, and Portal authentication</li> <li>DHCP snooping</li> <li>Dynamic ARP Inspection (DAI)</li> <li>IP Source Guard (IPSG)</li> </ul>

Item	Description
Maintenance features	<ul style="list-style-type: none"> <li>Unified management and maintenance on the Agile Controller</li> <li>Automatic login and configuration loading, and plug-and-play (PnP)</li> <li>Batch upgrade</li> <li>Telnet</li> <li>STelnet using SSH v2</li> <li>SFTP using SSH v2</li> <li>Local AP management through the serial interface</li> <li>Web local AP management through HTTP or HTTPS</li> <li>Real-time configuration monitoring and fast fault location using the NMS</li> <li>System status alarm</li> <li>Network Time Protocol (NTP)</li> </ul>


### Standards compliance

Item	Description
Safety standards	<ul style="list-style-type: none"> <li>UL 60950-1</li> <li>EN 60950-1</li> <li>CAN/CSA 22.2 No.60950-1</li> <li>IEC 60950-1</li> <li>GB 4943</li> </ul>
Radio standards	<ul style="list-style-type: none"> <li>ETSI EN 300 328</li> <li>RSS-210</li> <li>ETSI EN 301 893</li> <li>AS/NZS 4268</li> </ul>
EMC standards	<ul style="list-style-type: none"> <li>EN 301 489-1</li> <li>ICES-003</li> <li>GB 17625.1</li> <li>CISPR 22</li> <li>EN 301 489-17</li> <li>YD/T 1312.2-2004</li> <li>AS/NZS CISPR22</li> <li>CISPR 24</li> <li>ETSI EN 60601-1-2</li> <li>ITU k.20</li> <li>EN 55022</li> <li>CISPR 24</li> <li>IEC61000-4-6</li> <li>FCC Part 15</li> <li>GB 9254</li> <li>EN 55024</li> <li>IEC61000-4-2</li> </ul>
IEEE standards	<ul style="list-style-type: none"> <li>IEEE 802.11a/b/g</li> <li>IEEE 802.11h</li> <li>IEEE 802.11k</li> <li>IEEE 802.11w</li> <li>IEEE 802.11n</li> <li>IEEE 802.11d</li> <li>IEEE 802.11u</li> <li>IEEE 802.11r</li> <li>IEEE 802.11ac</li> <li>IEEE 802.11e</li> <li>IEEE 802.11v</li> </ul>
Security standards	<ul style="list-style-type: none"> <li>802.11i, Wi-Fi Protected Access 2(WPA2), WPA</li> <li>802.1X</li> <li>Advanced Encryption Standards(AES), Temporal Key Integrity Protocol(TKIP)</li> <li>EAP Type(s)</li> </ul>
EMF	<ul style="list-style-type: none"> <li>CENELEC EN 62311</li> <li>RSS-102</li> <li>CENELEC EN 50385</li> <li>FCC Part1&amp;2</li> <li>OET65</li> <li>FCC KDB series</li> </ul>
RoHS	Directive 2002/95/EC & 2011/65/EU
REACH	Regulation 1907/2006/EC
WEEE	Directive 2002/96/EC & 2012/19/EU


### AP7052DN Antennas Pattern




2.4G (PHI=0)




2.4G (PHI=90)




5G-1 (PHI=0) (2.4G-to-5G switchover )



5G-1 (PHI=90) (2.4G-to-5G switchover )



5G-2 (PHI=0)



5G-2 (PHI=90)

### Professional Service and Support

Huawei WLAN planning tools deliver expert network design and optimization services using the most professional simulation platform in the industry. Backed by fifteen years of continuous investment in wireless technologies, extensive network planning and optimization experience, and rich expert resources, Huawei helps customers:

- Design, deploy, and operate a high-performance network that is reliable and secure.
- Maximize return on investment and reduce operating expenses.

### More Information

For more information, please visit <http://e.huawei.com> or contact your local Huawei office.



Enterprise Services



Product Overview



Marketing Documentation

**Copyright © Huawei Technologies Co., Ltd. 2017. All rights reserved.**

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

#### **Trademark Notice**

 , HUAWEI, and  are trademarks or registered trademarks of Huawei Technologies Co., Ltd. Other trademarks, product, service and company names mentioned are the property of their respective owners.

#### **General Disclaimer**

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

HUAWEI TECHNOLOGIES CO.,LTD.  
Huawei Industrial Base  
Bantian Longgang  
Shenzhen 518129,P.R.China  
Tel: +86 755 28780808

[www.huawei.com](http://www.huawei.com)