Juniper EX4300-24T

Datasheet

Product Overview

- The Juniper EX4300-24T is a fixed 1U Ethernet switch for enterprise campus aggregation, data center access, and high-density wired networks.
- It provides 24 × 10/100/1000BASE-T non-PoE access ports for workstations, servers, phones, cameras, and other wired endpoints.
- Four built-in 40GbE QSFP+ ports support high-speed interconnection and Virtual Chassis operation, while an optional module adds four 1/10GbE SFP+ ports.
- The non-PoE model uses a 350W AC power supply and fits deployments where endpoint power is supplied locally or through separate equipment.
- The switch delivers 224Gbps unidirectional switching capacity, 448Gbps bidirectional capacity, and 333Mpps Layer 2/Layer 3 throughput.
- Junos OS, redundant field-replaceable fans and power supplies, and Virtual Chassis support up to ten switches for resilient network growth.

Product Highlights

- **24-Port Gigabit Access:** Twenty-four 10/100/1000BASE-T ports provide dense non-PoE Gigabit access for enterprise and campus endpoints.
- **40GbE Virtual Chassis Ports:** Four built-in QSFP+ ports provide 40GbE connectivity for switch interconnection or Virtual Chassis deployment.
- **Optional 1/10GbE Uplink Module:** The EX-UM-4X4SFP module adds four SFP+ ports that support 1GbE or 10GbE transceivers.
- **Non-PoE 350W AC Design:** The EX4300-24T uses a 350W AC power supply for access deployments that do not require integrated endpoint power.

Detailed Features



EX4300-24T

Quote | Help

Component	Specification
Access Ports	24 × 10/100/1000BASE-T
Built-in Uplink/VCP Ports	4 × 40GbE QSFP+
Optional Uplink Module	EX-UM-4X4SFP, 4 × 1/10GbE SFP+
PoE Support	Not supported
Switching Capacity	224 Gbps unidirectional / 448 Gbps bidirectional

Dense Non-PoE Gigabit Access

The EX4300-24T provides 24 10/100/1000BASE-T ports in a fixed 1U chassis for enterprise and campus access deployments that use separate endpoint power.

Built-in 40GbE Interconnection

Four QSFP+ ports provide 40GbE connectivity and can be used as Virtual Chassis ports or as network ports with suitable optics and cables.

Optional 1/10GbE Expansion

The EX-UM-4X4SFP uplink module provides four ports that accept 1GbE SFP or 10GbE SFP+ transceivers, allowing the uplink mix to match the network design.

Efficient 350W AC Power

The non-PoE model uses a JPSU-350-AC-AFO-A 350W AC supply, avoiding the larger power budget required by PoE variants.

Ten-Member Virtual Chassis

The EX4300 family supports up to ten switches in one logical Virtual Chassis, simplifying management and enabling resilient campus architectures.

Junos OS and Modular Operations

Junos OS provides modular switching and routing functions, with graceful process restart and operational tools for enterprise networks.

Layer 2 and Layer 3 Scale

The platform supports VLANs, spanning-tree features, link aggregation, ACLs, IPv4/IPv6 routing, multicast routing, and a 64K MAC address table.

Redundant Field-Replaceable Design

Two fan modules and up to two load-sharing, hot-removable AC power supplies support front-to-back airflow and simplified serviceability.

Technical Specifications

Product Specifications

Feature	Value
Product Model	EX4300-24T
Product Type	Fixed 1U Ethernet access and aggregation switch
Operating System	Junos OS
Access Ports	24 × 10/100/1000BASE-T
Built-in Network Ports	4 × 40GbE QSFP+
Optional Uplink Module	EX-UM-4X4SFP, 4 × 1/10GbE SFP+
Virtual Chassis Port Count	4
Virtual Chassis Port Type	QSFP+
Virtual Chassis Scale	Up to 10 switches
Management Port	1 × RJ-45 management port
Console Ports	1 × RJ-45 console port + 1 × Mini USB Type B console port
USB Port	1 × USB Type-A port
PoE Support	Not supported
Power Supply	JPSU-350-AC-AFO-A 350W AC power supply; one standard, two supported
Power Redundancy	Load-sharing; hot-removable and hot-insertable

Feature	Value
Data Rate	224 Gbps unidirectional / 448 Gbps bidirectional
Packet Switching Capacity (64-byte packets)	224 Gbps unidirectional / 448 Gbps bidirectional
Throughput	333 Mpps (64-byte packets)
Module Slots	1
MAC Addresses	64,000
Jumbo Frames	9216 bytes
IPv4 Unicast Host Routes	32K
IPv4 Unicast Route Prefixes	16K
IPv4 Multicast Routes	16K
IPv6 Unicast Host Routes	15K
IPv6 Unicast Route Prefixes	4K
IPv6 Multicast Routes	16K
IPv6 Neighbor Discovery Entries	32K
ARP Entries	64K
VLAN IDs	1–4094 (4,093 VLAN IDs)
MSTP Instances	64
VSTP Instances	510
LAGs	128; up to 16 ports per LAG
CPU	1.5GHz dual-core PowerPC CPU
DRAM	2GB
Internal Storage	2GB
Cooling	2 × hot-removable EX4300-FAN modules; front-to-back airflow
Dimensions (W × H × D)	17.36 × 1.72 × 16.38 in (44.09 × 4.37 × 41.61 cm)
Depth with Field-Replaceable Units	17.51 in (44.48 cm)
Chassis Weight	13 lb (5.9 kg) spare chassis
Operating Temperature	0°C to 45°C
Storage Temperature	−40°C to 70°C
Operating Humidity	10% to 85% noncondensing
Nonoperating Humidity	0% to 95% noncondensing
Operating Altitude	Up to 10,000 ft / 3,048 m

Feature	Value
Nonoperating Altitude	Up to 16,000 ft / 4,876 m
Airflow Direction	Front-to-back (AFO)

Product Comparison

Feature	EX4300-24T	EX4300-24P	EX4300-48T
Access port configuration	24 × 10/100/1000BASE-T	24 × 10/100/1000BASE-T PoE+	48 × 10/100/1000BASE-T
Built-in QSFP+ ports	4 × 40GbE	4 × 40GbE	4 × 40GbE
Optional uplink module	EX-UM-4X4SFP, 4 × 1/10GbE SFP+	EX-UM-4X4SFP, 4 × 1/10GbE SFP+	EX-UM-4X4SFP, 4 × 1/10GbE SFP+
PoE support	Not supported	IEEE 802.3at PoE+	Not supported
Maximum PoE budget	Not applicable	720W with two PSUs	Not applicable
Data rate	224/448 Gbps	224/448 Gbps	248/496 Gbps
Throughput	333 Mpps	333 Mpps	369 Mpps
Virtual Chassis scale	Up to 10 switches	Up to 10 switches	Up to 10 switches
Power supply	1 × 350W AC PSU standard; 2 supported	1 × 715W AC PSU standard; 2 supported	1 × 350W AC PSU standard; 2 supported
Airflow	Front-to-back	Front-to-back	Front-to-back
Best-fit deployment	Non-PoE campus aggregation or access	PoE campus aggregation or access	High-density non-PoE access

Accessories

Category	Accessories
Included Accessories	- JPSU-350-AC-AFO-A 350W AC power supply
	- 2 × EX4300-FAN fan modules
	- AC power cord for the installation region
Optional Accessories	- Additional JPSU-350-AC-AFO-A AC power supply for redundancy

Category	Accessories
	- EX-UM-4X4SFP 4-port 1/10GbE SFP+ uplink module
	- 40GbE QSFP+ transceivers and DAC cables; optics and cables sold separately

Support & Warranty

24/7 Online Service

3-Year Premium Warranty

Professional Technical Support

100% Low Price Guarantee

100% Quality Assurance

100% Money Back Guarantee

About Us



Router-switch.com, headquartered in Hong Kong since 2002, has been a trusted global leader in ICT distribution for 20+ years. We provide cutting-edge networking, cybersecurity, data center, and AI solutions to meet evolving business needs. Our wide range includes products from top brands like Cisco, Arista, Aruba, Fortinet, Mellanox, and Huawei, ensuring access to the latest technology and innovations.

21,500+ global customers

600,000+ end-users

200+ countries & regions

20+ years experience

500+ global vendors

100,000+ SKUs available

700+ local sales experts

50-98% off global list prices

Contact Us

Email

Sales Inquiries: sales@router-switch.com
Expert Technical Support: ccie-support@router-switch.com
Cooperative Partnerships: partner@router-switch.com

Follow Us

Facebook: @Routerswitchdotcom
LinkedIn: Router-switch.com
X: @routerswitchcom
Instagram: @routerswitchdotcom

Phone

USA: +1-626-655-0998
Hong Kong: +852-25925389 / +852-25925411

Global Footprint

Global Warehouses & Service Centers Across Continents.



Global Branches

Hong Kong Branch

Rm 605, 6/F, Fa Yuen Comm Bldg, 75-77 Fa Yuen St, Mongkok, Kowloon, Hong Kong, China

Shenzhen Branch

Jingfeng Building, 1001 Shangbu South Road, Futian District, Shenzhen, China

USA Branch

35 E Horizon Ridge Pkwy, Ste 110 #30131, Henderson, NV 89002, USA

UK Branch

Third Floor, 207 Regent Street, London W1B 3HH, UK

References

[1] Juniper Networks. (n.d.). EX4300 Switch Hardware Guide. Retrieved November 16, 2026, from https://www.juniper.net/documentation/us/en/hardware/ex4300/ex4300.pdf

[2] Juniper Networks. (n.d.). EX4300 Hardware Specifications. Retrieved November 16, 2026, from https://apps.juniper.net/hct/product/EX4300/hwspecs