### TL:Tapo-C200 Datasheet

Get a Quote



### Overview

TP-Link Tapo C200 Rotary Home Security WiFi Camera.

#### **Quick Spec**

Table 1 shows the quick spec.

Product Code	TP-Link Tapo C200 Rotary Home Security WiFi Camera
Security	128 bit AES encryption with SSL/TLS
Wireless Rate	11Mbps(802.11b) 54Mbps(802.11g) 150Mbps(802.11n)
Frequency	2.4 GHz
Wireless Security	WEP, WPA/WPA2-PSK
Video Compression	H.264
Frame Rate	15fps
Video Streaming	1080p
Regulatory Certification	FCC, IC, CE, NCC
System Requirements	iOS 9+, Android 4.4+

#### **Product Details**

TP-Link Tapo C200 Rotary Home Security WiFi Cameraprovides these features and benefits:

High-Definition Video: Records every image in crystal-clear 1080p definition

Pan and Tilt: 360° horizontal and 114° vertical range

Advanced Night Vision: Provides a visual distance of up to 30 ft

Motion Detection and Notifications: Notifies you when the camera detects movement

Sound and Light Alarm: Trigger light and sound effects to frighten away unwanted visitors.

Two-Way Audio: Enables communication through a built-in microphone and speaker

Safe Storage: Locally stores up to 128 GB on a microSD card, equal to 384 hours (16 days) of footage. (Based on laboratory conditions)

Voice Control: Free Up Your Hands with Voice Control: Works with the Google Assistant and Amazon Alexa. (Google Assistant and Amazon Alexa are not available in all languages and countries)

#### **Compare to Similar Item**

Table 2 shows the comparison.

Product Code	TP-Link Tapo C200 Rotary Home Security WiFi Camera	TP-Link Tapo C210 2K 1296p Pan/Tilt Home Security WiFi Camera
Security	128 bit AES encryption with SSL/TLS	128 bit AES encryption with SSL/TLS
Wireless Rate	11Mbps(802.11b) 54Mbps(802.11g) 150Mbps(802.11n)	11Mbps(802.11b) 54Mbps(802.11g) 72.2Mbps(802.11n)
Frequency	2.4 GHz	2.4 GHz
Wireless Security	WEP, WPA/WPA2-PSK	WPA/WPA2-PSK
Video Compression	H.264	H.264

Frame Rate	15fps	15fps
Video Streaming	1080p	3MP
Image Sensor	1/2.9"	1/2.8"
Resolution	1080p Full HD	3MP (2304 x 1296)
Lens	F/NO: 2.4; Focal Length: 4mm	F/NO: 2.4; Focal Length: 3.83mm
Night Vision	850 nm IR LED up to 30 ft	850 nm IR LED up to 30 ft
View Range	360° horizontal, 114° vertical	360° horizontal, 114° vertical

#### **Get More Information**

Do you have any question about the TP-Link Tapo C200 Rotary Home Security WiFi Camera?

Contact us now via Live Chat or sales@router-switch.com.

# Specification

TP-Link Tapo C200 Rotary Home Security WiFi Camera Specification		
NETWORK		
Security	128 bit AES encryption with SSL/TLS	
Wireless Rate	11Mbps(802.11b) 54Mbps(802.11g) 150Mbps(802.11n)	
Frequency	2.4 GHz	
Wireless Security	WEP, WPA/WPA2-PSK	
ACTIVITY NOTIFICATIONS		
Input Trigger	Motion detection	
Output Notification	Push notification	
VIDEO		
Video Compression	H.264	
Frame Rate	15fps	
Video Streaming	1080p	
SYSTEM		
Regulatory Certification	FCC, IC, CE, NCC	
System Requirements	iOS 9+, Android 4.4+	
ENVIRONMENT		
Operating Temperature	0°C~40°C (32°F~104°F)	
Storage Temperature	-40°C~70°C (-40°F~158°F)	
Operating Humidity	10%~90%RH non-condensing	
Storage Humidity	5%~90%RH non-condensing	

Moniting Plate Camera Base           HARDWARE           Buton         Reset button           Indicator LED         System LED           Adepter Input         00-240VAC, 50/60Hz, 0.3A           Adepter Output         9.0V/0.6A           Dimensions (W x D x H)         3.4 x 3.3 x 4.6 in. (86.6 x 85 x 117.7 mm)           CAMERA         1/2.9°           Image Sensor         1/2.9°           Resolution         5/00 p Full HD           Index Fund         5/00 p Full HD           Index Fund         5/00 p Full HD           Lens         5/00 p Full HD           Night Vision         800 m IR LED up to 30 ft           View Range         300° horizontal, 114° vertical           AUDIO         2/way audio	PACKAGE CONTENTS		
Button         Reset button           Indicator LED         System LED           Adapter Input         100-240VAC, 50/60Hz, 0.3A           Adapter Output         9.0V/0.6A           Dimensions (W x D x H)         3.4 x 3.3 x 4.6 in. (86.6 x 85 x 117.7 mm)           CAMERA         1/2.9"           Resolution         1080p Full HD           Inge Sensor         1/10.2 4.; Focal Length: 4mm           Night Vision         850 nm IR LED up to 30 ft           View Range         360° horizontal, 114° vertical           AUDIO         2*way audio	Package Contents	Power Adapter Quick Start Guide Mounting Screws Mounting Plate	
Indicator LED       System LED         Adapter Input       100-240VAC, 50/60Hz, 0.3A         Adapter Output       9.0V/0.6A         Dimensions (W x D x H)       3.4 x 3.3 x 4.6 in. (86.6 x 85 x 117.7 mm)         CAMERA       1/2.9"         Inage Sensor       1/2.9"         Resolution       1080p Full HD         Lens       F/NO: 2.4; Focal Length: 4mm         Night Vision       850 nm IR LED up to 30 ft         View Range       360° horizontal, 114° vertical         AUDIO       2-way audio	HARDWARE		
Adapter Input     100-240VAC, 50/60Hz, 0.3A       Adapter Output     9.0V/0.6A       Dimensions (W x D x H)     3.4 x 3.3 x 4.6 in. (86.6 x 85 x 117.7 mm)       CAMERA     1/2.9"       Image Sensor     1/2.9"       Resolution     1000 Full HD       Lens     F/NO: 2.4; Focal Length: 4mm       Night Vision     850 nm IR LED up to 30 ft       View Range     360° horizontal, 114° vertical       AUIOC     2-way audio	Button	Reset button	
Adapter Output9.0V/0.6ADimensions (W x D x H)3.4 x 3.3 x 4.6 in. (86.6 x 85 x 117.7 mm)CAMERA1/2.9"Image Sensor1/2.9"Resolution1080p Full HDLens5/NO: 2.4; Focal Length: 4mmNight Vision850 nm IR LED up to 30 ftView Range360° horizontal, 114° verticalAUDO2-way audio	Indicator LED	System LED	
Dimensions (W x D x H)     3.4 x 3.3 x 4.6 in. (86.6 x 85 x 117.7 mm)       CAMERA     Inage Sensor       Inage Sensor     1/2.9"       Resolution     1080p Full HD       Lens     F/NO: 2.4; Focal Length: 4mm       Night Vision     850 nm IR LED up to 30 ft       View Range     360° horizontal, 114° vertical       AUDIO     2-way audio	Adapter Input	100-240VAC, 50/60Hz, 0.3A	
CAMERA         image Sensor       1/2.9"         Resolution       1080p Full HD         Lens       F/NO: 2.4; Focal Length: 4mm         Night Vision       850 nm IR LED up to 30 ft         View Range       360° horizontal, 114° vertical         AUDIO       2-way audio	Adapter Output	9.0V/0.6A	
Image Sensor       1/2.9"         Resolution       1080p Full HD         Lens       F/NO: 2.4; Focal Length: 4mm         Night Vision       850 nm IR LED up to 30 ft         View Range       360° horizontal, 114° vertical         AUDIO       2-way audio	Dimensions (W x D x H)	3.4 x 3.3 x 4.6 in. (86.6 x 85 x 117.7 mm)	
Resolution       1080p Full HD         Lens       F/NO: 2.4; Focal Length: 4mm         Night Vision       850 nm IR LED up to 30 ft         View Range       360° horizontal, 114° vertical         AUDIO       2-way audio	CAMERA		
Lens       F/NO: 2.4; Focal Length: 4mm         Night Vision       850 nm IR LED up to 30 ft         View Range       360° horizontal, 114° vertical         AUDIO       2-way audio	Image Sensor	1/2.9"	
Night Vision       850 nm IR LED up to 30 ft         View Range       360° horizontal, 114° vertical         AUDIO       2-way audio	Resolution	1080p Full HD	
View Range     360° horizontal, 114° vertical       AUDIO     2-way audio	Lens	F/NO: 2.4; Focal Length: 4mm	
AUDIO Audio Communication 2-way audio	Night Vision	850 nm IR LED up to 30 ft	
Audio Communication 2-way audio	View Range	360° horizontal, 114° vertical	
	AUDIO		
Audio Input & Output Built-in microphone and speaker	Audio Communication	2-way audio	
	Audio Input & Output	Built-in microphone and speaker	

### Want to Buy

Order Now

Get a Quote

### Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of Cisco, Huawei, HPE, Dell, Hikvision, Juniper, Fortinet, etc.

200+ Countries we Sold R 18,000+ Customers Trusted



50%-98% Off Global List Price



## Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com